

SAFETY DATA SHEET

Randolph Float Sealer

1 – IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

PRODUCT NAME: **Randolph Float Sealer**
PRODUCT NUMBER: 20-FS
RECOMMENDED USE: Aircraft coatings and cleaners
RESTRICTIONS ON USE: Not applicable
SUPPLIER: Consolidated Aircraft Coatings
P.O. Box 3129, Riverside, CA 92519, USA
4343 Fort Drive, Riverside, CA 92509, USA
(951) 684-4280
(951) 809-7144
(760) 782-1947
EMERGENCY TELEPHONE: (800) 424-9300 (Chemtrec- US)
(703) 527-3887 (International – Call Collect)

2 - HAZARDS IDENTIFICATION

GHS Hazard Category

Flammable liquid- Category 2
Eye Irritation - Category 2A
Skin Irritation- Category 2
Respiratory Irritation- Category 3
Specific target organ toxicity (single exposure) – Category 3, Central Nervous System H336

Label Elements

Pictograms



Signal Word

DANGER

Hazard Statements

Highly flammable. Irritating to eyes and skin
May cause drowsiness or dizziness
Harmful: danger of serious damage to health by prolonged exposure through inhalation
Possible risk of harm to the unborn child
Harmful: may cause lung damage if swallowed

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Store in a well-ventilated place. Keep container tightly closed. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist/vapors/spray. Use only outdoors or in a well-ventilated area. Vapors may cause drowsiness and dizziness.

Response

INHALATION:
Move the victim to a fresh air place immediately. Get medical attention if discomforts persist.

INGESTION:

Rinse mouth with clean water immediately. DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, keep the victim's head low so that vomits from the stomach will not enter the lungs.

SKIN CONTACT:

Remove contaminated clothing and flush the affected skin areas with clean water for at least 15 minutes. Get medical attention if discomforts persist.

EYES CONTACT:

Make sure all contact lenses are removed before flushing the eyes with eye lids open with clean water for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

Storage

Store in a well-ventilated Place. Keep container tightly closed. Keep cool. Store in a locked cabinet, cage or room.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Highly flammable. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness.

CLASSIFICATION (1999/45) Xi, F, R11, R36, R66, R67

3 – COMPOSITION /INFORMATION ON INGREDIENTS

Name	EC No.	CAS No.	Content %	Classification (67/548/EEC)
Methyl Ethyl Ketone	201-159-0	78-93-3	70-80%	XI, F, R11, R36, R66, R67, S16, S9
Isopropyl Alcohol	200-661-7	67-63-0	20-30%	XI, F, R11, R36, R67, S16, S24/25, S26, S7

The Full Text for all R-Phrases and S-Phrases is displayed in Section 15

COMPOSITION COMMENTS

The data shown are in accordance with the latest EC Directives.

4- FIRST AID MEASURES**NOTICE:**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Irritating to eyes, skin, nose and throat. Headache, dizziness and nausea can result from inhalation. Repeated or prolonged skin contact may result in dryness possibly leading to dermatitis. Central nervous system effects including excitation, euphoria, contracted eye pupil dizziness, blurred vision, fatigue, nausea, headache, loss of consciousness, respiratory arrest and sudden death could occur of long term and/or high concentration exposures vapors.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Contact with the skin or eyes may cause irritation. Prolonged or repeated contact can cause moderate irritation, defatting and/or dermatitis. Skin and eyes should be flushed with water for at least 15 minutes.

INGESTION HEALTH RISK AND SYMPTOMS OF EXPOSURE:

Toxic if ingested. May affect liver, kidneys or blood. MEK has caused cancer in certain animal tests. Preexisting eye, skin, heart, central nervous system and respiratory disorders may be aggravated by exposure to this product.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Overexposure may cause anesthesia, headache, nausea or dizziness. Breathing the vapors may irritate the nose and throat. Detectable amounts of chemicals or substances known to the state of California to cause cancer, birth defects, or other reproductive harm may be found in this product. Use care when handling chemical and petroleum products even though they are water reducible.

CARCINOGENICITY: NTP CARCINOGEN: N/A IARC MONOGRAPHS: N/A OSHA REGULATED: N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE TO THIS PRODUCT:

Preexisting eye, skin, heart, central nervous system and respiratory disorders may be aggravated by exposure to this product.

EMERGENCY AND FIRST AID PROCEDURES:

Remove victim to fresh air and restore breathing if required. Call a physician if required. If breathing stops, give artificial respiration. Keep person warm. Never give anything by mouth to an unconscious person. Vapors will irritate the nose and throat. For eye splash, flush with water for at least 15 minutes. For skin splash, wash with soap and water and remove contaminated clothing. Consult physician if irritation persists. If ingested, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. If spontaneous vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Consult physician or poison control center immediately.

5- FIRE FIGHTING PROCEDURES

EXTINGUISHING MEDIA:

Alcohol foam, CO₂, Dry Chemical

SPECIAL FIREFIGHTING PROCEDURES:

Isolate from heat, sparks, electrical equipment and open flame. Water is not usually effective in fighting liquid fires. Do not enter a confined area without full bunker gear including a positive-pressure NIOSH-approved self-contained breathing apparatus.

Decomposition products may form toxic materials.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Water spray may be used to cool closed containers to help prevent explosion when exposed to extreme heat. Never use welding or cutting torch on or near drum (even empty) because residue or product can ignite explosively. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by pilot lights, flames and other ignition sources at locations distant from the material handling point. Flammable material.

6-ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Wear protective clothing as described in Section 8.

ENVIRONMENTAL PRECAUTIONS:

Spillages or uncontrolled discharges into watercourses must immediately be alerted to Environmental Agency or other appropriate regulatory authority.

SPILL CLEANUP METHODS:

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, open flames, and smoking. Ventilate. Absorb in vermiculite, dry sand, or earth and place into containers for disposal.

7-HANDLING AND STORAGE

USAGE PRECAUTIONS:

Keep away from heat, sparks and open flames. Avoid spilling, skin and eyes contact. Use with adequate ventilation and avoid excessive exposure to solvent vapors. Use approved respirator if air contamination exceeds the accepted level.

STORAGE PRECAUTIONS:

FLAMMABLE/Combustible. Keep away from oxidizers, open flames and other ignition sources. Keep unused contents in original container and tightly closed lids. Store in a cool, dry and well-ventilated place and at an ambient Temperature not to exceeding above 120° F.

STORAGE CLASS:

FLAMMABLE liquid storage.

8-EXPOSURE CONTROL/PERSONAL PROTECTION

Name	Workplace Exposure Limits	Remarks
Methyl Ethyl Ketone	ACGIH: 200ppm TWA; 300ppm STEL NIOSH: 200ppm TWA;590 mg/m ³ TWA; 3000ppm IDLH OSHA –Final PELs: 200ppm TWA; 590 mg/m ³ TWA	Consult local authorities for acceptable exposure limits.
Isopropyl Alcohol	ACGIH: 200 ppm TWA; 400 ppm STEL NIOSH: 400 ppm TWA; 980 mg/m ³ TWA 2000 ppm IDLH (10% LEL) ;OSHA-Final PELs: 400 ppm TWA; 980 mg/m ³ TWA	Same As Above

**PROTECTIVE EQUIPMENTS:****PROCESS CONDITIONS:****ENGINEERING MEASURES:****RESPIRATORY EQUIPMENT:****HANDPROTECTION:****EYE PROTECTION:****OTHER PROTECTION:****HYGIENE MEASURES:**

Provide eyewash station.

Provide adequate ventilation. Fully equipped spray booth is recommended to ensure the workers legal exposure limits are not exceeded.

Wear respirator with appropriate cartridge for organic solvents and chemicals.

Wear approved gloves such as Neoprene, Nitrile or Rubber types.

Wear splash-proof goggles.

Wear appropriate clothing to prevent any possible skin contact.

DO NOT SMOKE IN THE WORK AREA. Wash at the end of each work shift and before eating, drinking or smoking. Promptly remove contaminated clothing.

9- PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid
COLOR:	Clear
ODOR:	Ketone characteristics
BOILING POINT:	133-252° F
RELATIVE DENSITY:	0.900 g/mL
VAPOR DENSITY:	Heavier than air
FLASH POINT:	24.0 °F (Closed Cup)
FLAMMABILITY LIMITS:	1.0 % (Lower) N.A. % (Upper)
SOLUBILITY VALUE (g/100g H ₂ O @ 20°C):	Insoluble
VOLATILE ORGANIC COMPOUND (VOC):	665 g/L

10- STABILITY AND REACTIVITY**STABILITY:**

Stable

CONDITIONS TO AVOID:

None reasonably foreseeable.

INCOMPATIBILITY (MATERIALS TO AVOID):

If product contains aluminum, do not contaminate with acids, caustics, chlorinated hydrocarbons or oxidizers as these materials will react with aluminum to produce hydrogen and heat. Incompatible with strong alkalis or strong oxidizers. This material may dissolve some plastics, rubber compounds or coatings. May react strongly with acids while in liquid form.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:Mostly CO₂ with some CO.**HAZARDOUS POLYMERIZATION:**

N/A

11-TOXICOLOGICAL INFORMATION

Methyl Ethyl Ketone (CAS# 78-93-3): Draize test, rabbit, skin: 500 mg/24H Moderate; Draize test, rabbit, skin: 402 mg/24H Mild; Inhalation, mouse: LC50 = 32 gm/m³/4H; Inhalation, rat: LC50 = 23500 mg/m³/8H; Oral, mouse: LD50 = 4050 mg/kg; Oral, rat: LD50 = 2737 mg/kg; Skin, rabbit: LD50 = 6480 mg/kg;

Carcinogenicity: Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.

Epidemiology: No information available.

Teratogenicity: Embryo or Fetus: fetotoxicity, ihl-rat TCLo=1000 ppm. Specific Developmental Abnormalities: craniofacial and urogenital, ihl-rat TCLo=3000 ppm/7H; musculoskeletal, ihl-rat TCLo=1000 ppm.

Reproductive Effects: No information available.

Neurotoxicity: No information available.

Mutagenicity: Sex chromosome loss/non-disjunction: *S. cerevisiae* 33800 ppm.

Other Studies: See actual entry in RTECS for complete information.

Isopropyl Alcohol (CAS#67-63-0): LD50/LC50: Draize test, rabbit, eye: 100 mg Severe; Draize test, rabbit, eye: 10 mg Moderate; Draize test, rabbit, eye: 100 mg/24H Moderate; Draize test, rabbit, skin: 500 mg Mild; Inhalation, mouse: LC50 = 53000 mg/m³; Inhalation, rat: LC50 = 16000 ppm/8H; Inhalation, rat: LC50 = 72600 mg/m³; Oral, mouse: LD50 = 3600 mg/kg; Oral, mouse: LD50 = 3600 mg/kg; Oral, rabbit: LD50 = 6410 mg/kg; Oral, rat: LD50 = 5045 mg/kg; Oral, rat: LD50 = 5000 mg/kg; Skin, rabbit: LD50 = 12800. Carcinogenicity: Not listed by ACGIH, IARC, NTP, or CA Prop 65. Epidemiology: No information found. Teratogenicity: A rat & rabbit developmental toxicity study showed no teratogenic effects at doses that were clearly maternally toxic. In a separate rat study, no evidence of developmental neurotoxicity was associated with

gestational exposures to IPA up to 1200 mg/kg/d. Reproductive Effects: See actual entry in RTECS for complete information. Mutagenicity: See actual entry in RTECS for complete information. Neurotoxicity: In rats exposed to isopropanol by inhalation, acute neurotoxicity was noted at 1 and 6 hours at 5000 ppm, but only minimal effects were seen at 1500 ppm and the animals recovered within 5 hours. No toxicity was noted at 500 ppm.

12- ECOLOGICAL INFORMATION

Methyl Ethyl Ketone (CAS#78-93-3): Ecotoxicity : Fish/Fathead Minnow/LC50 = 3220mg/l; Environmental : Substance evaporates in water with T1/2=3D (rivers) to 12D (lakes); Physical : Substance photodegrades in air with T1/2=2.3 days.

Isopropanol (CAS#67-63-0): Ecotoxicity: Fish: Fathead Minnow: >1000 ppm; 96h; LC50Daphnia: >1000 ppm; 96h; LC50Fish: Gold orfe: 8970-9280 ppm; 48h; LC50 IPA has a high biochemical oxygen demand and a potential to cause oxygen depletion in aqueous systems, a low potential to affect aquatic organisms, a low potential to affect secondary waste treatment microbial metabolism, a low potential to affect the germination of some plants, a high potential to biodegrade (low persistence) with unacclimated microorganisms from activated sludge. Environmental: No information available. Physical: THOD: 2.40 g oxygen/gCOD: 2.23 g oxygen/gBOD-5: 1.19-1.72 g oxygen/g Other: No information available.

13 – DISPOSAL CONSIDERATIONS

Hazardous wastes should be sent to a RCRA approved incinerator or disposed of in a RCRA approved waste facility. Dispose of container and unused contents in accordance with federal, state and local requirements.

I certify that all chemicals in this shipment comply with all applicable rules or orders under TSCA and that I am not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.

14 – TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: **Randolph Float Sealer**
PRIMARY HAZARD CLASS/DIVISION: **3**
UN/UA NUMBER: **UN1263**
PACKING GROUP: **II**

IMO PROPER SHIPPING NAME: **PAINT**
IMO UN CLASS: **3**
IMO UN NUMBER: **1263**
IMO PACKING GROUP: **II**
IMO LABEL: **FLAMMABLE LIQUID**
IMO VESSEL STOWAGE: **B**

Air shipping this product is not advised and if done must be handled by a certified carrier according to IATA rules.



GHS LABEL:

DANGER

HIGHLY FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL OR FATAL IF SWALLOWED AND ENTERS AIRWAYS.

Refer to SDS for additional information on safe handling / use. - Keep out of reach of children. For Industrial Use Only.

Contains: Methyl Ethyl Ketone (70-80%), and Isopropyl Alcohol (20-30%). This product contains one or more chemicals known to the State of California to cause cancer, birth defects, and/or other reproductive harm.

Hazards: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to organs.

Precautionary Statement(s): Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Store in a well-ventilated place. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist/vapours/spray. Use only outdoors or in a well-ventilated area. Ground/bond container and receiving equipment.

First Aid: Inhalation - Move person to fresh air. If symptoms occur obtain medical attention. **Skin Contact** - Wash affected skin with soap and water. If symptoms occur obtain medical attention. **Eye Contact** - If substance has got into the eyes, immediately wash out with plenty of water for at least 15 minutes. If symptoms occur obtain medical attention. **Ingestion** - Do not induce vomiting. Drink one glass of water. If symptoms occur obtain medical attention.

15 – REGULATORY INFORMATION

Hazards: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to organs.

Precautionary Statement(s): Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Store in a well-ventilated place. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist/vapours/spray. Use only outdoors or in a well-ventilated area. Ground/bond container and receiving equipment.

CODES:



XI



F

- XI=irritant
- F=highly flammable

R-Phrases:

R11: Highly Flammable
R36: Irritating to eyes
R66: Repeated exposure may cause skin dryness or cracking
R67: Vapors may cause drowsiness and dizziness

S-Phrases:

S7: Keep container tightly closed
S9: Keep container in a well-ventilated place
S16: Keep away from sources of ignition - No smoking
S24/25: Avoid contact with skin and eyes
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

16- DISCLAIMER

Above information is based on data supplied to us and is believed to be correct. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose. It is the user's obligation to determine the safe use of it.