

SAFETY DATA SHEET

Poly-Tone Reducer

1 – IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

PRODUCT NAME: **Poly-Tone Reducer**
PRODUCT NUMBER: R65-75

SUPPLIER: Poly-Fiber, Inc.
P.O. Box 3129, Riverside, CA 92519, USA
4343 Fort Drive, Riverside, CA 92509, USA
(951) 684-4280
(951) 809-7144
(760) 782-1947

EMERGENCY TELEPHONE: (800) 424-9300 (Chemtrec- US)
(703) 527-3887 (International – Call Collect)

2 - HAZARDS IDENTIFICATION

GHS Hazard Category

Flammable liquid	Category 2
Eye Irritation	Category 2A
Skin Irritation	Category 2
Respiratory Irritation	Category 3
Specific target organ toxicity (single exposure) –	Category 3, Central Nervous System
Specific target organ toxicity (repeated exposure) -	Category 2
Reproductive toxicity	Category 2
Aspiration hazard	Category 1
Acute toxicity, Inhalation	Category 4
Acute toxicity, Dermal	Category 4
Acute toxicity, Oral	Category 4
Carcinogenicity	Category 2
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

Label Elements

Pictograms



Signal Word

DANGER

Hazard Statements

⚠ WARNING: This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poison Schedule:	6
Australian Inventory of Chemical Substances (AICS)	Listed
New Zealand Inventory of Chemicals (NZIoC)	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB 76)	16

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H227 Combustible liquid
 H302 + H332 Harmful if swallowed or if inhaled
 H304 May be fatal if swallowed and enters airways.
 H312 + H332 Harmful in contact with skin or if inhaled
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H361 Suspected of damaging fertility or the unborn child
 H373 May cause damage to organs through prolonged or repeated exposure.
 H401 Toxic to aquatic life
 H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal

P501 Dispose of contents/ container to an approved waste disposal plant.

3 – COMPOSITION /INFORMATION ON INGREDIENTS

Name	EC No.	CAS No.	Content %	GHS Classification
Toluene	203-625-9	108-88-3	50-60%	Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure (Category 2), H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401

Methyl Isobutyl Ketone	203-550-1	108-10-1	10-20%	Flammable liquids (Category 3), H226 Acute toxicity, Inhalation (Category 4), H332 Acute toxicity, Dermal (Category 4), H312 Skin irritation (Category 2), H315 Carcinogenicity (Category 2), H351 Specific target organ toxicity - repeated exposure (Category 2), H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411
Methyl n-Amyl Ketone	203-767-1	110-43-0	10-20%	Flammable liquids (Category 3), H226 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332
Ethylene Glycol Mono-n-propyl Ether	220-548-6	2807-30-9	10-20%	Flammable liquids (Category 3), H226 Acute toxicity, Dermal (Category 4), H312 Eye irritation (Category 2A), H319
Glycol Ether EB	203-905-0	111-76-2	0-10%	Flammable liquids (Category 4), H227 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332 Acute toxicity, Dermal (Category 4), H312 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319

The Full Text for all H-Statements and P-Statements is displayed in Section 15

COMPOSITION COMMENTS

The data shown are in accordance with the latest GHS Directives.

4- FIRST AID MEASURES

INHALATION:

Move the victim to a fresh air place immediately. Get medical attention if discomforts persist.

INGESTION:

Rinse mouth with clean water immediately. DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, keep the victim's head low so that vomits from the stomach will not enter the lungs.

SKIN CONTACT:

Remove contaminated clothing and flush the affected skin areas with clean water for at least 15 minutes. Get medical attention if discomforts persist.

EYES CONTACT:

Make sure all contact lenses are removed before flushing the eyes with eye lids open with clean water for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

5- FIRE FIGHTING PROCEDURES

EXTINGUISHING MEDIA:

Fire can be extinguished by using Foam, carbon dioxide, or dry powder, Dry Chemicals, sand, dolomite, etc...

SPECIAL FIREFIGHTING PROCEDURES:

Do not use a direct stream of water. Product may float and can be reignited on the surface of the water. Do not enter a confined area without full bunker gear including a positive-pressure NIOSH-approved self-contained breathing apparatus. Decomposition products may form toxic materials.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Never use welding or cutting torch on or near drum (even empty) because residue or product can ignite explosively. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by pilot lights, flames and other ignition sources at locations distant from the material handling point. Flammable material.

6-ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Wear protective clothing as described in Section 8.

ENVIRONMENTAL PRECAUTIONS:

Spillages or uncontrolled discharges into watercourses must immediately be alerted to Environmental Agency or other appropriate regulatory authority.

SPILL CLEANUP METHODS:

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, open flames, and smoking. Ventilate. Absorb in vermiculite, dry sand, or earth and place into containers for disposal.

7-HANDLING AND STORAGE**USAGE PRECAUTIONS:**

Keep away from heat, sparks and open flames. Avoid spilling, skin and eyes contact. Use with adequate ventilation and avoid excessive exposure to solvent vapors. Use approved respirator if air contamination exceeds the accepted level.

STORAGE PRECAUTIONS:

FLAMMABLE/Combustible. Keep away from oxidizers, open flames and other ignition sources. Keep unused contents in original container and tightly closed lids. Store in a cool, dry and well-ventilated place and at an ambient Temperature not to exceeding above 120°F.

STORAGE CLASS:

FLAMMABLE liquid storage.

8-EXPOSURE CONTROL/PERSONAL PROTECTION

Name	Workplace Exposure Limits	Remarks
Toluene	ACGIH: 20 ppm TWA NIOSH: 100 ppm TWA; 375 mg/m ³ TWA 500 ppm IDLH OSHA-Final PELs: 200 ppm TWA; 300 ppm Ceiling	Consult local authorities for acceptable exposure limits.
Methyl Isobutyl Ketone	ACGIH: 50 ppm; 75 ppm STEL NIOSH: 50 ppm TWA; 205 mg/m ³ TWA 500 ppm IDLH OSHA-Final PELs: 100 ppm TWA; 410 mg/m ³ TWA	Same As Above
Methyl N-Amyl Ketone	ACGIH: 50 ppm TWA OSHA: 100 ppm TWA	Same As Above
Glycol Ether EB	ACGIH: 20 ppm TWA NIOSH: 5 ppm TWA; 24 mg/m ³ TWA 700 ppm IDLH OSHA-Final PELs: 50 ppm TWA; 240 mg/m ³ TWA	Same As Above
Ethylene Glycol Mono-n-propyl Ether	None established	Same As Above

**PROTECTIVE EQUIPMENTS:****PROCESS CONDITIONS:****ENGINEERING MEASURES:****RESPIRATORY EQUIPMENT:****HANDPROTECTION:****EYE PROTECTION:****OTHER PROTECTION:****HYGIENE MEASURES:**

DO NOT SMOKE IN THE WORK AREA. Wash at the end of each work shift and before eating, drinking or smoking. Promptly remove contaminated clothing.

Provide eyewash station.

Provide adequate ventilation. Fully equipped spray booth is recommended to ensure the workers legal exposure limits are not exceeded.

Wear respirator with appropriate cartridge for organic solvents and chemicals.

Wear approved gloves such as Neoprene, Nitrile or Rubber types.

Wear splash-proof goggles.

Wear appropriate clothing to prevent any possible skin contact.

9- PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE:**

Liquid

COLOR:

Clear

ODOR:

Ketone odor

BOILING POINT:

172-345° F

RELATIVE DENSITY:

0.849 g/mL

VAPOR DENSITY: Heavier than air
FLASH POINT: 43 °F (Closed Cup)
FLAMMABILITY LIMITS: NA
SOLUBILITY VALUE
(g/100g H₂O @ 20°C): Insoluble
VOLATILE ORGANIC COMPOUND
(VOC): 864 g/L

10- STABILITY AND REACTIVITY

STABILITY:

Stable

CONDITIONS TO AVOID:

Heat and fires. Ignition sources.

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong alkalis or strong oxidizers. This material may dissolve some plastics, rubber compounds or coatings. May react strongly with acids while in liquid form.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Hydrogen chloride and very small amounts of phosgene and chlorine.

HAZARDOUS POLYMERIZATION:

N/A

11-TOXICOLOGICAL INFORMATION

Toluene (CAS# 108-88-3): ACGIH: A4-Not Classifiable as a Human Carcinogen; IARC: Group 3 carcinogen; No other toxicological information available

Methyl Isobutyl Ketone (CAS#108-10-1): LD50/rat/oral = 2080mg/kg; Carcinogenicity: Not listed by NTP or IARC.

Methyl n-Amyl Ketone (CAS#110-43-0): LD50/rabbit/dermal = 12.6mL/kg; LD50/rat/oral = 1600mg/kg; Carcinogenicity: Not listed by IARC, NTP or OSHA.

Glycol Ether EB (CAS#111-76-2): Carcinogenicity: Not listed by NTP, IARC or OSHA.

Ethyl.Glyc.Monopropyl Ether (CAS#2807-30-9): LD50/rat/oral=3089mg/kg, LD50/mouse/oral=1774 mg/kg, LC50/rat/6 hrs > 2132 ppm, LD50/rabbit/dermal=1337 mg/kg, Skin Irritation/guinea pig=slight, Skin Irritation/rabbit=slight, Eye Irritation/rabbit=strong, Skin Sensitization/guinea pig=none.

12- ECOLOGICAL INFORMATION

Toluene (CAS#108-88-3): Ecotoxicity : No data available; Environmental : From soil, substance evaporates and is microbially biodegraded. In water, substance volatilizes and biodegrades; Physical: Photo chemically produced hydroxyl radicals degrade substance.

Methyl Isobutyl Ketone (CAS#108-10-1): Ecotoxicity : Not expected to be toxic to terrestrial life; Environmental : substance evaporates and biodegrades when released to soil, water and air.

Methyl n-Amyl Ketone (CAS#110-43-0): Ecotoxicity: No data available.

Glycol Ether EB (CAS#111-76-2): Ecotoxicity: Not expected to be toxic to aquatic life. Environmental: substance evaporates and biodegrades when released to soil, water and air.

Ethyl.Glyc.Monopropyl Ether (CAS#2807-30-9) : Oxygen Demand Data: BOD-5:1.3 g/g; BOD-20: 1.6 g/g COD (Chemical Oxygen Demand):: 2.04 g/g ThBOD: 1.98 g/g Acute Aquatic Effects Data: 96 h LC-50 (fathead minnow): > 91.3 mg/l NOEC: 91.3 mg/l, 96 h LC-50 (daphnid): > 91.3 mg/l NOEC: 91.3 mg/l, 96 h LC-50 (flatworm): > 91.3 mg/l NOEC: 91.3 mg/l, 96 h LC-50 (snail): > 91.3 mg/l NOEC: 91.3 mg/l

13 – DISPOSAL CONSIDERATIONS

Hazardous wastes should be sent to a RCRA approved incinerator or disposed of in a RCRA approved waste facility. Dispose of container and unused contents in accordance with federal, state and local requirements.

I certify that all chemicals in this shipment comply with all applicable rules or orders under TSCA and that I am not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.

14 – TRANSPORT INFORMATION

DOT / ADR / RID Classification:**DOT PROPER SHIPPING NAME:****PAINT RELATED MATERIAL****PRIMARY HAZARD CLASS/DIVISION: 3****UN/UA NUMBER:****UN1263**

PACKING GROUP: II

IMDG and ADN Classification:

IMDG PROPER SHIPPING NAME: PAINT RELATED MATERIAL
 IMDG UN CLASS: 3
 IMDG UN NUMBER: UN1263
 IMDG PACKING GROUP: II
 IMDG LABEL: FLAMMABLE LIQUID
 IMDG VESSEL STOWAGE: B

Air shipping this product is not advised and if done must be handled by a certified carrier according to IATA rules.

15 - REGULATORY INFORMATION

⚠️ WARNING: This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poison Schedule:	6
Australian Inventory of Chemical Substances (AICS)	Listed
New Zealand Inventory of Chemicals (NZIoC)	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB 76)	16



GHS LABEL:

DANGER

HIGHLY FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. CAUSES SERIOUS EYE DAMAGE. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL OR FATAL IF SWALLOWED AND ENTERS AIRWAYS.

Refer to SDS for additional information on safe handling / use. - Keep out of reach of children. For industrial use only.

Contains: Toluene (50-60%), Methyl Isobutyl Ketone (10-20%), Methyl n-Amyl Ketone (10-20%), Ethylene Glycol Mono-n-propyl Ether (10-20%) , and Glycol Ether EB (0-10%).

Hazard Statements

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H227 Combustible liquid
 H302 + H332 Harmful if swallowed or if inhaled
 H304 May be fatal if swallowed and enters airways.
 H312 + H332 Harmful in contact with skin or if inhaled
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child
H373 May cause damage to organs through prolonged or repeated exposure.
H401 Toxic to aquatic life
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal

P501 Dispose of contents/ container to an approved RCRA waste disposal plant.

16- DISCLAIMER

Above information is based on data supplied to us and is believed to be correct. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose. It is the user's obligation to determine the safe use of it.